

## Tomato Greenhouse TG 1

Art.-No.: 36.513.15

Bar code: 4006825573558

Sales unit: 1 pc

The Tomato Greenhouse consists of statically proper calculated aluminium profiles. The individual parts which must be installed are limited to a minimum. A patent-registered connecting system and fixed connection points reduce the assembling time significantly. Heat-insulating, full-page from aluminium profiles bordered 4 mm sheets made of polycarbonate offers an optimal climate in the tomato greenhouse.

It is recommended to embody the tomato greenhouse with 4 pcs ground anchors (as special accessory available) in the ground. The national customary building regulation is to be considered.

The tomato greenhouse is snow load tested with 50 kg/m<sup>2</sup> and wind load tested with 25 kg/m<sup>2</sup>.

### Features:

- High strength, statically proper calculated aluminium profiles for an optimal reinforcement of geometry
- Patent-registered connecting system
- Polycarbonate sheets 4 mm impact and shock resistant, resistant to ball throw, UV-resistant, temperature resisting -25°C to +60°C
- 2 pcs large, smooth-running sliding doors

### Technical data:

- Breadth: 132 cm
- Depth: 69 cm
- Eaves height: 145.7 cm
- Ridge height: 184.1 cm
- Door height (clearance): 174 cm
- Door breadth (inner width): 2x 64.5 cm
- Floor space approx.: 0.91 m<sup>2</sup>
- Room volume: 1.5 m<sup>3</sup>
- Thickness sheets: 4 mm
- Net weight: 13.5 kg
- Gross weight: 19 kg



Quick & Easy system –  
singular assembly technique

### As special accessory available:

**Ground anchors BD4 Set** Art.-No.: 36.405.90

Bar code: 4006825514551