

Split-Air Conditioner SPLIT 850 C

Art.-No.: 23.651.66

Bar-Code: 4006825534696

Sales unit: 1 pc

One area – Split-Air Conditioner for wall installation with the functions: Cooling and dehumidifying, time programming device for ON/OFF.

Complete with remote control and 4 m cooling agent connecting tubes with flexible insulation (max. 15 m possible at professional installation).

Easy installation of the air conditioner with a **cooling capacity of 2,500 W**. Ideal for rooms until approx. 80 m³. The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level.

Fan speed with a maximum speed of 420 m³/h.

With the **automatic dehumidification** the units evaporates from its surrounding max. **1.0 l/h** of excess humidity.

Timer for programme settings, Automatic- and night functions.

All functions can be set with the **remote control**. Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

Dimensions:

Indoor unit (WxHxD): 710x180x250 mm
Outdoor unit (WxHxD): 720x260x430 mm

Weight:

Indoor unit: 11 kg
Outdoor unit: 27 kg

Packing dimensions indoor unit: 750x260x320 mm

Packing dimensions outdoor unit: 765x350x500 mm

Features:

- LED display (1)
- Air escape lamella (2)
- Air suction grid (3)
- Remote control (4)
- Fan (5)
- Pipe connection

Technical data:

- Coolant:	R407C
- Energy-Efficiency-Class:	D
- EER / COP:	2.62 / -
- Energy consumption at cooling:	480 kWh / Year
- Cooling capacity:	2,500 W
- Air throughput:	420 m ³ /h
- Capacity of humidity reduction max:	1.0 l/h
- Mains:	220 - 240 V ~ 50 Hz
- Refrigerant quantity:	500 g for 4 m pipe
- Noise level:	Indoors: ≤ 37 dB (A) Outdoors: ≤ 52 dB (A)

Characteristics according to EN 14511

