



## Pillar drill SB 1625/1 D

Art.-No.: **42.512.11**

Bar code: 4006825507126

Sales unit: 1 pc

Pillar drill with V-belt. The table can continuously be adjusted, lateral tilting and turning either side. Spindle is set on ball bearing, depth gauge setting. ON/OFF switch with no-load function, electrical contacts in the V-belt housing as additional protection and folding eye shield. This model is standard equipped with a vice. The Pillar drill has also an left/right switch. With the 12-fold speed graduation you can make the rotary speed suitable for every material

### Features:

- Switcher with zero voltage-releasing (1)
- Hinged chip guard (2)
- Drill table (tiltable, pivoting) (3)
- Adjustable depth stop (4)
- Table heights adjustment (5)
- Vice (6)
- Fast climbing drill chuck (7)



### Technical Data:

- Nominal voltage: 400 V ~ 50Hz
- Power rating: 700 W (S2 15 min.)
- Motor speed: 1400 min<sup>-1</sup>
- Spindle speed: 12 step 210 – 2220 min<sup>-1</sup>
- Angular motion drill table: -45° until + 45°
- Quick chuck: Ø 3 until 16 mm
- Drill chuck mount: B16
- Drill spindle conus: MK 2
- Throat: 169 mm
- Drill depth: 80 mm
- Pillar diameter mm: 70 mm
- Size of base table: 450 x 265 mm
- Size of drill table: 260 x 260 mm
- Heights: approx. 1590 mm
- Weights: 63 kg
- Packing dimension: 1145 x 465 x 295 mm