

Features

- 230 V socket for easy power supply (1)
- Overload switch for appliance safety (2)
- Reversing starter to start the machine (3)
- Sturdy feet (4)
- Carrying handle for easy transport (5)
- Powerful 2-stroke engine, air-cooled
- Synchronous generator
- Large 4.2 liter tank for a continuous operation
- Full crank shaft
- Automatic voltage regulation

Technical Data

- | | |
|----------------------------|---------------------------------|
| ■ Generator: | Synchronous |
| ■ Continuous power: | 650 W |
| ■ Maximum power: | 720 W (S2 15 min) |
| ■ Rated voltage: | 230 V / 1 ~ |
| ■ Rated current: | 2.8 A / 1 ~ |
| ■ Frequency: | 50 Hz |
| ■ Type: | 1 cylinder; 2-stroke air-cooled |
| ■ Cylinder capacity: | 63 cm ³ |
| ■ Max. Power: | 0.95 kW / 1.3 HP |
| ■ Fuel: | Mixture 1:50 (2%) (Oil:Petrol) |
| ■ Tank capacity: | 4.2 l |
| ■ Consumption at 2/3 load: | approx. 0.7 l/h |
| ■ Protection type: | IP 23 |
| ■ Spark plug: | NGK BPR5ES |
| ■ Net weight: | 18.2 kg |
| ■ Gross weight: | 18.5 kg |
| ■ Packing dimensions: | 382 x 325 x 310 mm |
| ■ Bar code: | 4006825 553420 |
| ■ Sales unit: | 1 pc |

