

Electric welding transformers are especially suitable for joining by welding of flat-iron, angle iron, tubes or similar material. One great advantage of electric welding is that the materials might not be warmed up and welding can be started directly at the requested position. Work pieces with various strength can also be welded with each other without any problems.

Features

- Thermal cut-out with control light (1)
- Continuously adjustable welding current (2)
- Welding shield (3)
- Produced to Europe standard EN 60974-1
- Adaptor cable (4)
- Chipping hammer (5)
- Steel brush (6)
- Universal electrodes (7)
- 2 Angle magnets (8)
- Mobile

Technical Data

- | | |
|------------------------|------------------------------------------------|
| ■ Mains: | 230/400 V ~ 50 Hz |
| ■ Fuse: | 16 A |
| ■ Welding current: | 57 – 200 A |
| ■ Weldable electrodes: | Ø 2 – 4 mm |
| ■ Idle speed: | 48 V |
| ■ Electrodes: | 30 pcs Ø 2.0 x 300 mm
30 pcs Ø 2.5 x 350 mm |
| ■ Net weight: | 21.0 kg |
| ■ Gross weight: | 25.0 kg |
| ■ Packing dimensions: | 500 x 265 x 330 mm |
| ■ Bar code: | 4006825 551976 |
| ■ Sales unit: | 1 pc |

