

Scroll Saw DKS 405/1 E

Art.-No.: **43.090.10**

Bar code: **4006825501216**

Sales unit: **1 pc**

Precise, complicated work on wood, plastic, aluminium, plexi glass or gypsum are challenges for model construction and handicrafts. With the stable parallel arm it is easy to saw accurately straightforward. The flexibility of the DKS 405/1 E points itself when working to the millimetre range, sawing perfect round forms and circles out. A blower device removes the dust particles directly from the working piece. The transparent saw blade protection offers optimal security without disturbing the work. For mitre cuts you can adjust the workbench up to 45 degrees.

Features:


- Saw dust blower facility (1)
- Stroke rate electronic (2)
- No-voltage switch (3)
- Connection for dust extraction (4)
- Adapter for leave saw blades (5)

Technical data:


- Mains: 230 V ~ 50 Hz
- Power: 120 watts S2 5 min
- Idle speed n_0 : 400 – 1600 min⁻¹
- Stroke height: 21 mm
- Saw blade length: 127 mm
- Cutting height max.: 57 mm / 90°; 27 mm / 45°
- Throat depth: 406 mm
- Table size: 410 x 253 mm
- Table tiltable: 0° bis 45°
- Footprint: 410 x 245 mm
- Weight: 14.4 kg
- Packing dimensions: 640 x 310 x 333 mm

Transmitting height:

50 mm / 90° at max. throat depth
10 mm / 45° at max. throat depth



5



As special accessory available:

Spare saw blade
(Set 5 pcs)

Art.-No.: **45.062.00**

Bar code: **4006825453928**

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4309010_01046.doc

Erstelldatum / create date: 16.11.2006 14:46:00

Aktualisiert / up dated: 29.11.2006