



Einhell

HGG 300 Niro Heating Generator

Art.-No. 23.309.10

Heating generators from EINHELL offers advanced technology and usual solid quality at a fair price. Due to the high efficiency design and construction of the unit it could be kept small and handy with a high heating power. The normal connection is to a 5 resp. 11 kg propane gas bottle. The integrated piezo ignition as well as the thermal cut-out warrants a safe operation. The unit is suitable for example for heating well ventilated rooms, the drying of new buildings for spot heating of jobs and things like this. A gas hose and the pressure reducer are supplied as standard equipment.

The device is suitable for commercial use! (Attention! Commercial use only with the supplied pressure reducer or excess flow cut-off valve according to DIN 30693!)

Features

- Housing made of stainless steel (1)
- Carrying handle (2)
- Heating reflector made of galvanized sheet steel (3)
- ON / OFF switch for fan (4)
- Gas valve button
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable
- Gas hose
- Pressure reducer 1.5 bar with excess flow cut-off valve

Technical Data

- | | |
|----------------------------|------------------------|
| ■ Mains: | 230 V ~ 50 Hz, 38 W |
| ■ Nominal heat load: | 30 kW |
| ■ Nominal air volume: | 500 m ³ /h |
| ■ Nominal gas consumption: | 2150 g/h liquid gas P |
| ■ Operating pressure: | 1.5 bar |
| ■ Type of gas: | propane acc. DIN 51622 |
| ■ Product weight: | 4.7 kg |

Logistic Data

- | | |
|-----------------------|--------------------|
| ■ Net weight: | 4.9 kg |
| ■ Gross weight: | 6.0 kg |
| ■ Packing dimensions: | 470 x 230 x 330 mm |
| ■ Bar code: | 4006825 237078 |
| ■ Sales unit: | 1 pc |



CE 0085

