

## Features

- 230 V socket for easy power supply
- Overload switch for appliance safety
- Reversing starter to start the machine
- Sturdy feet for safe standing
- Carrying handle for easy transport
- Powerful 2-stroke engine, air-cooled
- Synchronous generator
- Large 4.2 liter tank for a continuous operation
- Full crank shaft
- Automatic voltage regulation



## Technical Data

- Type of generator	Synchronous
- Frequency	50 Hz
- Continuous power (S1) at 230 V	650 W
- Max. power (S2   S2time) at 230 V	720 W   2 min
- Nominal current at 230 V	2.8 A
- 230 V socket	1 Pieces
- Engine	two-stroke, air cooled
- Number of cylinders	1 Pieces
- Engine displacement	63 cm <sup>3</sup>
- Engine speed	3000 min <sup>-1</sup>
- Max. engine power	1.5 kW
- Fuel	Mixture
- Capacity of fuel tank	4.2 L
- Running time with 2/3 load	7 h
- Sound power level LWA	90 dB (A)

## Logistic Data

- Product weight	16.3 kg
- Gross weight single packaging	17.4 kg
- Dimensions single packaging	380 x 320 x 335 mm
- Pieces per export carton	1 Pieces
- Gross weight export carton	16.5 kg
- Dimensions export carton	380 x 320 x 335 mm
- Container quantity (20"/40"/40"HC)	756   1512   1512