

## Electric Hoist SHZ 125/250-1 Bavaria

Art.-No.: **22.551.10**

Bar-Code: 4006825221237

Sales Unit: 2 pcs

The Einhell electric hoist offers you a multiplicity of advantages:

The start button is equipped with an **emergency-cut-off button**. This device guarantees a safe cut-off in case of failure of the start switch.

- The start button is designed in **insulation class II** (safety insulated).
- A **forcibly actuated end switch** assures that the hoist will safely be cut-off at the upper end (i. e. in case the 2 contacts stick together).
- **Improved brake:** In case of a defect on the pressure spring (i. e. rupture of the wire) stopping of the load still is assured.
- The brake will be activated in case of power failure in the motor.
- The **non-rotating steel rope** reduces twisting of the loads during the lifting motion.
- The load hook with **additional safety latch**: This added latch prevents an unintended loosening of the load suspension device.
- The **motor with overload protection** prevents it from overheating.

### Features:

- Fastening with 2 double clamps
- Start button with emergency button
- Deflection pulley with payload hook
- 12 m non-rotating (kinking) steel wire  
Ø 3,18 mm
- Motor with thermal cut-out
- An automatic brake secures the load in any position

### Technical data:

- Payload: 125 kg without pulley  
250 kg with pulley
- Lifting height: approx.. 11,5 m without pulley  
approx.. 5,7 m with pulley
- Mains: 230 V ~ 50 Hz
- Power: 550 W S3 25 %
- Rope speed: 10 m/min without pulley  
5 m/min with pulley
- Weight: 11,5 kg
- Dimensions : 350 x 220 x 140 mm



Emergency-cut-off button

Safety latch

### As special accessory available:

Hoist lever arm  
Global SA 1200

Art.-No.: **22.553.96**  
Bar-Code: 4006825221244

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved  
File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\2255110\_01025.doc

Erstelldatum / create date: 21.02.2005 11:38:00

Aktualisiert / up dated: 28.03.2008