



## Submersible Pump RSP 2562

Art.-No.: **41.702.92**

Bar code: **4006825556155**

Sales unit: **4 pcs**

By the low weight the submersible pump is ideal to empty flooded basements, tanks and containers, etc. The installed float switch controls the ON/OFF functions of the pump. High quality standard at materials and constructional design, e. g. a stainless high-grade steel drive shaft warrants a maintenance-free operation and durable application. The housing is made of an impact resistant plastic.

### Features:

- Handle (1)
- Universal connection for 1" and 1 1/4" male thread hose connection as well as 1" male thread (2)
- 90 ° angel bracket with 1 1/2" x 1 1/2" male thread (3)
- Float switch (4)



### Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 250 W
- Delivery quantity max.: 6,200 l/h
- Delivery height max.: 5.5 m
- Immersions depth max.: 5 m
- Water temperatur max.: 35°C
- Foreign particle size up to: Ø 3 mm
- Mains cable: 10 m H05RN-F
- ON function: approx. 50 cm
- OFF function: approx. 5 cm
- Connection hose: 1 1/2" female thread
- Net weight: 4 kg
- Gross weight: 4.4 kg
- Packing dimensions: 220 x 160 x 310 mm

### Performance data:

Delivery height:	Delivery quantity:
1 m	max. 4,800 l/h
2 m	max. 3,600 l/h
3 m	max. 2,400 l/h
4 m	max. 1,500 l/h

### As special accessory available:

PVC-drainage hose 10 m/1"  
Einhell Royal

Art.-No.: **41.737.11**  
Bar code: **4006825414707**

