

Perfect cuts, optimal reliability!

Einhell®

NEW GENERATION



The radial tile cutting machine can be mounted quickly on the serial type support stand and is therefore suitable for mobile as well as stationary service.

With its unit one can cut wall- and floor tile, split tiles etc. Angle and double mitre cuts are possible and also jolly cuts.

The diamond cutting disc is cooled with the integrated pump for cooling liquids and an almost dust free operation is possible.



TPR 201 Set Radial Tile Cutting Machine

Available as special accessory:

Diamond cutting disc:
Ø 200 x Ø 25,4 mm

Art.-No.: 43.011.75

Ident-No.: 01014

Bar-Code: 4006825 434361



Logistic Information:

Type:	TPR 201 Set	Sales unit:	1 pc
Art.-No.:	43.012.58	20°:	168 pcs
Ident-No.:	01016	40°:	340 pcs
Bar Code:	4006825 534481	40° HC:	-- pcs
Packing:	890 x 490 x 370 mm	Weight:	34 kg (gross)



Perfect cuts, optimal reliability!

Einhell®

NEW GENERATION



Continuously tiltable motor guidance settings 0° - 45°



Angle stop with scale for exact cuts



Large water pan with integrated water pump



RCD-plug

Features:

- RCD-Plug
- Motor guidance settings 0° - 45° and tilting
- Motor setting 4-fold ball bearings
- Sturdy feet
- Sturdy aluminium guide rail
- Angle stop with scale for exact cuts
- Work table with rubber mat
- Large water pan guaranteed dust free working
- Diamond disc
- Sturdy disc cover made of sheet steel
- Integrated water pump
- Second diamond cutting disc included

Technical Data:

- Mains: 230 V ~ 50 Hz
- Power: 800 watts
- Idle speed n_0 : 3000 min⁻¹
- Working table: 600 x 385 mm
- Working height: 700 mm
- Cutting depth max.: 90° - 30 mm / 45° - 25 mm
- Cutting length max.: 520 mm
- Mitre cuts: 0° - 45°
- Diamond disc: Ø 200 x Ø 25,4 mm
- Insulation class: IP 54

Logistic Information:

Type:	TPR 201 Set	Tool:	Radial Tile Cutting Machine
Art.-No.:	43.012.58	Sales unit:	1 pc
Ident-No.:	01016	20`:`	168 pcs
Bar Code:	4006825 534481	40`:`	340 pcs
Packing:	890 x 490 x 370 mm	40`:`HC:	-- pcs
		Weight:	34 kg (gross)

