

Table Saw TK 1500 E

Art.-No.: **43.407.51**

Bar code: **4006825532630**

Sales unit: **1 pc**

The TK 1500 E is suitable for multifunctional operations, such as length and cross cuts in wood, flake boards, panels, veneered or coated furniture slabs and plastics. Its compact construction, its easy transport and the high power make the table saw ideally suitable as circular saw for field working, e. g. on construction sites and for interior fittings. The unit can be tilted up to 45° for mitre and bevel cutting. With the sturdy undercarriage the table saw becomes a sturdy, free-standing circular saw and thus it can be used in optimally working height.

Features:

- Saw blade protection with splinters exhaust device (1)
- Parallel guide with aluminium rail (2)
- Loupe for number scale (3)
- Push stick with clamp
- Cross fence with angle scale (4)
- Saw blade angle adjustment (5)
- Saw blade height adjustment (6)
- Powder-coated housing
- Carbide tipped saw blade

Technical data:

- Power: 1500 watts, S6 40%
- Idle speed: 5700 min⁻¹
- Mains: 230 V ~ 50 Hz
- Cutting height 90° / 45°: 75 mm / 48 mm
- Saw blade: Ø 250 x Ø 30 x 2.4 mm
- Number of teeth: 24 teeth
- Motor rotation range: 0 – 45°
- Cross guide tiltable: 2 x 0 – 60°
- Table size: 640 x 446 mm
- Height without undercarriage: 300 mm
- Working height with undercarriage: 850 mm
- Connection for splinters exhaust: Ø 35 mm
- Weight: 25,5 kg
- Packing dimensions: 730 x 590 x 335 mm



As special accessory available:

Carbide tipped saw blade

Ø 250 x Ø 30 mm 24 teeth

Carbide tipped saw blade

Ø 250 x Ø 30 mm 48 teeth

Carbide tipped saw blade

Ø 250 x Ø 30 mm 60 teeth

Art.-No.: **43.111.10**

Bar code: **40068254431223**

Art.-No.: **43.111.11**

Bar code: **4006825431230**

Art.-No.: **43.111.13**

Bar code: **4006825503166**