



## Table Saw TK 1800 UV

Art.-No.: **43.406.41**

Bar Code: 4006825506594

Sales Unit: 1 pcs

The table saw TK 1800 UV is a profi machine, which is suitable not only for stationary use, but also for mobile application. The simple-installable extension table guarantees a wide work surface, whereby the length support can be used in total width. The TK 1800 UV is designed for multi-purpose application: ripping and crosscuts of lumber, chipboard, plywood, multiplex board and veneered sheets. Its compact construction, practical transport handling and its power make it ideally suitable for use in construction sites and for interior decorating work. The saw can be tilted up to 45° for mitre cuts. The cross cut fence can be left or right of the saw blade and is equipped for 2 different heights. It can of course be set on either side to +45°. The splitting wedge can be taken out for covered cuts.

### Features:

- Crimping flange to fix the parallel stop (1)
- Number scale with loupe (2)
- Push stick with clamp (3)
- Cross fence with angle adjustment (4)
- Toolless removable extension table (5)
- Anodizing table surface for better anti-friction property (6)
- Saw blade protection with splinter exhaust (7)
- Parallel stop with aluminium guide (8)
- Saw blade angle adjustment with scale (9)
- Splitting wedge for covering cuts (10)
- Powder-coated housing
- Carbide tipped saw blade
- Saw blade height adjustment

### Technical data:

- Motor: 1800 watts, S6 40 %
- Idle speed: 4800 min<sup>-1</sup>
- Mains: 230 V ~ 50 Hz
- Cutting height: 90 °: 73 mm  
45 °: 53 mm
- Saw blade: Ø 250 x Ø 30 x 2,4 mm, 24 teeth
- Motor rotation range: 0 - 45 °
- Cross fence tiltable: 2 x 0 - 45°
- Table size: 570 x 440 mm
- Table width extension left/right: 570 x 250 mm
- Table length extension back side: 400 x 440 mm
- Height without underframe: 360 mm
- Working height with underframe: 900 mm
- Tool Size without additional table (Wx Lx H): 670 x 455 x 1100 mm



### As special accessories available:

- Carbide tipped Sawblade  
Ø 250 x Ø 30 x 3,2 mm 24 teeth
- Carbide tipped Sawblade  
Ø 250 x Ø 30 x 3,2 mm 48 teeth
- Carbide tipped Sawblade  
Ø 250 x Ø 30 x 3,2 mm 60 teeth
- Carbide tipped Sawblade  
Ø 250 x Ø 30 x 3,2 mm 80 teeth

- Art.-No.: **43.111.10**  
Bar-Code: 40068254431223
- Art.-No.: **43.111.11**  
Bar-Code: 4006825431230
- Art.-No.: **43.111.13**  
Bar-Code: 4006825503166
- Art.-No.: **43.111.12**  
Bar-Code: 4006825431247