



# Einhell



**Booster Cable**

**BT-BO 25/1 A LED SP**

**Item No.: 2030365**

Ident No.: 11026

Bar Code: 4006825603514

The BT-BO 25/1 A LED SP jumper cable provides good service for jump starting petrol or diesel engines. The 4 pole clamps are fully insulated and equipped with LED lighting. The conductive material is made of 31.4 mm<sup>2</sup> aluminium (= 25 mm<sup>2</sup> copper cable). The safe jump starting function is guaranteed by the integrated surge protection which protects against harmful voltage peaks. Delivered in a practical carrying bag, the jumper cable is compliant with DIN 72553-25.

## Features & Benefits

- Jumper cables tested according to DIN 72553-25
- 4 all-insulated pole-pliers
- Conductive material made of 31.4 mm<sup>2</sup> alu (= 25 mm<sup>2</sup> copper cable)
- Pliers with LED-lighting
- Surge protection against harmful voltage peaks while jumpstarting
- Incl. carrying bag



## Technical Data

- |                                 |                      |
|---------------------------------|----------------------|
| - For petrol engines up to max. | 5500 cm <sup>3</sup> |
| - For diesel engines up to max. | 3000 cm <sup>3</sup> |
| - Cable length                  | 3.5 m                |
| - Cable cross section           | 31.4 mm <sup>2</sup> |
| - Testing current               | 350 A                |

## Logistic Data

- |                                      |                     |
|--------------------------------------|---------------------|
| - Product weight                     | 1.74 kg             |
| - Gross weight single packaging      | 1.79 kg             |
| - Dimensions single packaging        | 320 x 320 x 65 mm   |
| - Pieces per export carton           | 6 Pieces            |
| - Gross weight export carton         | 11.5 kg             |
| - Dimensions export carton           | 640 x 320 x 185 mm  |
| - Container quantity (20"/40"/40"HC) | 4344   9000   10578 |

