



The practical submersible pump for using rainwater.

With an infinitely height-adjustable floating switch so that the switching on/off height and the switching differential can be infinitely adjusted.

In addition, the floating switch can be fastened for use in continuous mode. The integrated floating switch and the storage compartment for the extension hose fastened to the pump make this rainwater barrel pump the highlight of the garden season.



GLRP 300 Rain barrel pump

Logistic information:

Type:	GLRP 300	Sales unit:	4 pcs
Art.-No.:	41.704.32	20':	1,280 pcs
Ident-No.:	01017	40':	2,640 pcs
Bar code:	23181168	40' HC:	3,080 pcs
Packing:	250 x 220 x 360 mm	Weight:	5.5 kg (brutto)





Features:

- Handle with integrated cable winder
- Infinitely adjustable floating switch
- High-quality pump housing made of impact-resistant plastic
- Pressure tubes 27, 29, and 32 cm
- Flexible suction tube with stopcock
- Storage compartment for storing the tubes

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 300 W
- Flow rate max.: 4,600 l/h
- Flow rate max. with extension tubes: 1,750 l/h
- Flow height max.: 11 m
- Submersion depth max.: 7 m
- Hose connection: 3/4" male thread
- Water temperature max.: 35°C
- Cable length: 10 m

Logistic informations:

Type:	GLRP 300	Tool:	Rain barrel pump
Art.-No.:	41.704.32	Sales unit:	4 pcs
Ident.-No.:	01017	20`:	1,280 pcs
Bar code:	23181168	40`:	2,640 pcs
Packing:	250 x 220 x 360 mm	40` HC:	3,080 pcs
		Weight:	5.5 kg (brutto)

