

Split Air Conditioner SKA 2503 Dual C+H

Art.-No.: 23.655.80

Bar code: 4006825550740

Sales unit: 1 pc

Air Coniditioner for **cooling and heating** for wall installation. **Automatic air dehumidification**. **Complete with remote control** and 2 x 4 m connection copper tubes (max. 2x 10 m possible) with insulating tube. **Time programming device for ON/OFF**. Easy installation of the air conditioner with a **cooling capacity of 2 x 2.850 W** and a **heating capacity of 2 x 2.850 W**. Ideal for two larger rooms until approx. 80 m³. The outdoor unit can be used by temperatures from 0°C up to +43°C. Due to the possibility of heating operating, the air conditioner can additionally also be used as „interseasonal heating“. The unit consists of 3 parts, an outdoor part and two for indoors, in order to allow quick cooling and warrant an optimal noise level. 3 Settings of fan speed with a maximum speed of 2 x 550 m³/h. With the **automatic air dehumidification** the units evaporates from its surrounding **max. 2 x 1.0 l/h** excess humidity. **Timer for program settings, automatic- and night functions**. All functions can be set by the **remote control** with LCD display. Motorized ventilation lamella in the indoor unit.

Technical data:

- Coolant: R410A
- Energy-efficiency-class: C
- EER / COP: 2.91 / 2.94
- Energy consumption when cooling: 2 x 490 kWh per year
- Cooling capacity: 2 x 2,850 W / 10,000 BTU/h
- Heating capacity: 2 x 2,850 W / 10,000 BTU/h
- Air performance: 2 x 550 m³/h
- Mains: 230 V ~ 50 Hz
- Capacity of humidity reduction max.: max. 2 x 1.0 l/h
- Quantity of coolant: approx. 2 x 900 g/ for 5 m tubes (for each metre add 20 g more coolant)
- Noise level: Indoors: ≤ 40 dB (A)
Outdoors: ≤ 57 dB (A)

Features:

- Fan (1)
- Pipe connection
- Air suction filter (2)
- LCD-display (3)
- Air escape lamellas (4)
- Remote control (5)
- 2x 2 pcs refrigerant lines 4 m

Tool dimensions / Weight:

- 2x Indoor unit (WxDxH): 750x260x315 mm / 8 kg
- 1x outdoor unit (WxDxH): 1,020x410x700 mm / 65 kg

Packing dimensions / Weight:

- 2x Indoor unit (BxTxH): 790x275x325 mm / 10 kg
- 1x outdoor unit (BxTxH): 1,100x450x755 mm / 70 kg

Characteristics according to EN 14511

