

# Submersible Pump

## PVSP 100/200

Art.-No.: 41.706.32

Bar code: 4006825534849

Sales unit: 4 pcs

The durable and high performance submersible pump is particularly suitable for the delivery of contaminated water. Contaminations with a diameter of 20 mm do not represent any problem for this pump. Apart from its typical operational area in excavations, this pump is suitable ideally for emptying garden ponds or swimming pools. **By its continuously height adjustable float switch is the submersible pump indispensable during inundations or water pipe burst.**

An advantage of the pump is the handle with integrated cable rolling for tidy storage and transport.

### Features:

- **Handle with integrated cable rolling (1)**
- Housing made of stainless steel (2)
- Universal connection 1 ½" external thread (3)
- **Continuously adjustable float switch (4)**

### Technical Data:

- Voltage: 230 V ~ 50 Hz
- Power: 1,000 watts
- Delivery capacity max.: 20,000 l/h
- Delivery height max.: 8 m
- Immersion depth max.: 5 m
- Hose connection: 1 ½" inside thread
- Water temperature max.: 35 °C
- Mains cable length: 10 m
- Foreign particle size max.: Ø 20 mm
- Weight: 6.0 kg
- Packing dimensions: 240 x 190 x 400 mm

### Performance data:

Delivery height:	Delivery capacity:
2 m	max. 18,200 l/h
4 m	max. 14,800 l/h
6 m	max. 10,400 l/h

