


Compact & powerful for outdoor use!

Einhell®




NEW GENERATION



The TKS 17/250 L circular bench saw has been designed for stationary and mobile application. The easy-to-install table extensions provide a large work surface. The TKS 17/250 L has been designed for multi-purpose applications: ripping and crosscuts of lumber, chipboard, plywood, multiplex board, veneered board and plastics. Thanks to its V-belt drive the table saw is very low-noise and smooth running. Its compact design, ease of handling during transport and its powerful performance make ideal for outdoor use, e.g. at construction sites and for interior decorating work. The saw can be tilted up to 45° for mitre cuts. The sturdy underframe turns the circular bench saw into a sturdy stand-alone saw which can be used at optimum working heights.



TKS 17/250 L Circular bench saw

Available as special accessory:	Carbide-tipped saw blade: Ø 250 x Ø 30 mm 24 teeth	Art. No.: 43.111.10 Ident. No.: 01023 Bar Code: 4006825 431223	
	Carbide-tipped saw blade: Ø 250 x Ø 30 mm 48 teeth	Art. No.: 43.111.11 Ident. No.: 01023 Bar Code: 4006825 431230	
	Carbide-tipped saw blade: Ø 250 x Ø 30 mm 60 teeth	Art. No.: 43.111.13 Ident. No.: 01013 Bar Code: 4006825 503166	

Logistic Information:

Type:	TKS 17/250 L	Sales unit:	1 pc
Art.-No.:	43.406.46	20``:	165 pcs
Ident.-No.:	01016	40``:	345 pcs
Bar Code:	4006825 533682	40``HC:	n.a. pcs
Packaging:	745 x 590 x 340 mm	Weight:	35.15 kg (gross)



Compact & powerful for outdoor use!

Einhell®

NEW GENERATION

Anodised table surface for advanced anti-friction properties

Saw blade protection with dust exhaust

Parallel stop with aluminium guide

Laser for perfect cuts

Powder coated extension table

Crimping flange to fix the parallel stop

Handle for easy transport

Cross fence with angle adjust-

Easy-to-mount underframe

Saw blade angle adjustment with scale

Saw blade height adjustment



Features:

- Powder coated extension table
- Powder-coated housing
- Saw blade angle adjustment with scale
- Saw blade height adjustment
- Cross fence with angle adjustment
- Anodised table surface for advanced anti-friction property
- Saw blade protection with dust exhaust
- Parallel stop with aluminium guide
- Lens for number scale
- Push stick with clamp
- Carbide-tipped saw blade
- Laser for perfect cuts

Technical Data:

- Mains: 230 V ~ 50 Hz
- Power: 1,700 watts S6 40%
- Idle speed n_0 : 4,800 min⁻¹
- Cutting height: 90 °: 73 mm
45 °: 53 mm
- Saw blade: Ø 250 x Ø 30 x 2.6 mm, 24 teeth
- Motor rotation range: 0 – 45°
- Cross fence, tiltable: 2 x 0 – 45°
- Table size: 626 x 445 mm
- Table width extension left/right: 626 x 250 mm
- Table length extension back side: 445 x 320 mm
- Height without underframe: 330 mm
- Working height with underframe: 900 mm
- Connection for dust exhaust: Ø 35 mm

Logistic Information:

Typ:	TKS 17/250 L	Tool:	Circular bench saw
Art.-No.:	43.406.46	Sales unit:	1 pc
Ident-No.:	01016	20`:	165 pcs
Bar Code:	4006825 533682	40`:	345 pcs
Packaging:	745 x 590 x 340 mm	40` HC:	n.a. pcs
		Weight:	35.15 kg (gross)

