



Submersible pump GLSP 1003

Art.-No.: 41.705.27

Bar code:

Sales unit: 4 pcs

The powerful and robust submersible pump for draining garden ponds, flooded basements and construction sites. Capable of handling foreign particles up to Ø 20 mm in size.

High quality with materials as example rust-free stainless steel – motor shaft and high-quality control leakage shaft seal provides as far as possible maintenance-free and long-lived use.

The optimal tuning between engine and paddle-wheel lead to an enormous effectiveness of the performance data.

Technical data:

- Mains: 230 V ~ 50 Hz
- Power: 1,000 W
- Delivery quantity max.: 20,000 l/h
- Delivery height max.: 8 m
- Immersion depth max.: 5 m
- Water temperature: up to 35 °C
- Foreign particles size: Ø 20 mm
- Main cable length: 10 m H07RN-F
- Switch point ON: approx. 50 cm
- Switch point OFF: approx. 5 cm
- Hose connection: 1 ½" female thread
- Type of protection: IP 68
- Weight: 7.7 kg
- Packing dimensions: 240 x 170 x 370 mm

Features:

- Handle (1)
- Float switch (2)
- 1 x 90 ° angel bracket 1 ½" male thread and 1 ¼" female thread (3)
- Universal connection for ¾", 1", 1 ¼" and 1 ½" hoses

Performance data:

Delivery height:	Delivery capacity
2 m	18,200 l/h
4 m	14,800 l/h
6 m	10,400 l/h

Scope of delivery: 5-parts connection kit

