


The profi water works unit pumps water from wells and cisterns automatically with stable water pressure. Toilets, washing machines and garden watering are just a few of its numerous applications. The vessel is made of corrosion resistant stainless steel, therefore not rusty colouring of the water supplied. Furthermore the garden pump is equipped with a pre-filter, which prevents that dirt arrives into the pump inside. The unit is powered by a sturdy asynchronous motor with thermal protection. The water works is supplied complete with pressure switch and pressure gauge.



Performance data:



Features

- Pressure switch
- Pressure gauge
- Stainless steel tank 20 ltr.
- Water drain plug
- On- and Off switch
- Return valve
- Integrated pre-filter
- 3 handles
- Connection for pressure hose made of stainless steel
- Connection for suction hose made of stainless steel
- Vent screw
- Large water filler opening



As special accessory available:

- Suction hose 4 m plastic
- Suction hose 7 m plastic
- Suction hose 4 m brass
- Suction hose 4 m high-quality plastic
- Suction hose 7 m brass
- Suction hose 7 m high-quality plastic

Art.No.:

- 41.736.10
- 41.736.20
- 41.736.30
- 41.736.35
- 41.736.40
- 41.736.45



Logistic Information

Type:	YGL N.G. 1101
Art.-No.:	41.734.41
Ident-No.:	01018
Bar code:	4006825 555219
Packing:	545 x 350 x 700 mm
Sales unit:	1 pc
20'':	207 pcs
40'':	423 pcs
40'' HC:	478 pcs
Net weight:	16.1 kg
Gross weight:	18.5 kg

Technical Data

■ Mains:	230 V ~ 50 Hz
■ Power:	1,100 W
■ Delivery capacity max.:	4,200 l/h
■ Delivery height max.:	48 m
■ Pressure max.:	4.8 bar
■ Activation pressure max.:	1.5 bar
■ Cut-off pressure max.:	3 bar
■ Tank volume:	20 l
■ Suction and pressure connection:	1" female thread
■ Water temperature max.:	35 °C
■ Suction height max.:	8 m