



BT-BC 15

Battery Charger

Item No.: 1075020

Ident No.: 11030

Bar Code: 4006825101478

The BT-BC 15 battery charger is a universal charger for 6-12-24 Volt motor vehicle batteries. The charging voltage and the 2-stage charging rate can be set by means of an easily accessible turn-switch. The inbuilt ampere meter allows the quick and safe reading of the current charging rate. The strong and totally insulated terminal clamps grant an optimal contact to the battery terminals at any time, and the device can be transported safely due to its handy, stable handle.

Features

- All-insulated construction
- Overload-, fals poling- and short circuit protection
- Sheet steel housing
- Carrying handle
- Turn-switch for quick/normal load+setting of the required voltage
- Built-in ammeter
- Mains cable with europe plug
- Charging leads with sturdy pole clamps



Technical Data

- Charging voltage 6 V/ 12V/ 24V
- Suitable for batteries (from min. Ah to max. Ah): 10-300 Ah
- Charging current Min. (arith./eff.) - Max. 4,4 / 6,5 - 10,4 / 15 A (arith./eff.) on 6 V d.c.
- Charging current Min. (arith./eff.) - Max. 5,4 / 8 - 10,4 / 15 A (arith./eff.) on 12 V d.c.
- Charging current Min. (arith./eff.) - Max. 4,7 / 7 - 6,8 / 10 A (arith./eff.) on 24 V d.c.
- Mains supply 230 V | 50 Hz



Logistic Data

- Product weight 5.45 kg
- Gross weight single packaging 6.11 kg
- Pieces per export carton 2 Pieces
- Gross weight export carton 13 kg
- Dimensions single packaging 335 x 255 x 175 mm
- Dimensions export carton 540 x 345 x 190 mm
- Container quantity (20"/40"/40"HC) 1622 | 0 | 0

