

### Features

- 36 mm tube system (1)
- Handle with cable winding (2)
- 50 l stainless steel vessel (3)
- 2 large transport wheels (4)
- Water drain screw (5)
- 2 fixable guide rollers (6)
- Carrying handle (7)
- Blow adaptor (8)
- Integrated female connector with automatic function (Falling delay 5 seconds) (9)
- Accessory bracket (10)

### Technical data

- |                        |                    |
|------------------------|--------------------|
| ■ Mains voltage:       | 230 V ~ 50 Hz      |
| ■ Input power:         | 1,400 W            |
| ■ Female connector:    | max. 2,200 W       |
| ■ Length suction tube: | 2.5 m              |
| ■ Vessel capacity:     | 50 l               |
| ■ Net weight:          | 11.4 kg            |
| ■ Gross weight:        | 14.8 kg            |
| ■ Packing dimensions:  | 525 x 490 x 670 mm |
| ■ Bar code:            | 4006825 552119     |
| ■ Sales unit:          | 1 pc               |

### Standard accessories

- 1 suction hose 2.5 m Ø 36 mm (1)
- 1 pleated filter (11)
- 1 foam filter (12)
- 2-piece suction tube (13)
- Handle with air regulator (14)
- Component adaptor (15)
- 1 crevice nozzle (16)
- Floor nozzle with 3 attachments (17)
- 1 Tank bag

