



RED


RT-SS 120 L

Scroll Saw

Precise, complicated work on wood, plastic, aluminium, plexi glass or gypsum are challenges for model construction and hand-crafts.

With the stable parallel arm it is easy to saw accurately straight-forward. The flexibility of the RT-SS 120 L points itself when working to the millimetre range, sawing perfect round forms and circles out.

A blower device removes the dust particles directly from the working piece. The transparent saw blade protection offers optimal security without disturbing the work. For mitre cuts you can adjust the workbench up to 45 degrees to the right or left side. A flexible LED light cares for the right illuminating. The scroll saw is equipped moreover with a laser, for precise and straight cuts.



Features

- Stroke rate electronic
- Integrated saw dust blower facility
- Laser for precise and straight cuts
- Saw table swivelling 2 x 45°
- Flexible LED-Light for exactly illuminate of the workpieces
- Integrated tool compartment for saw blades
- No-voltage switch
- Adapter for leave saw blades
- Saw table made of massive cast steel
- Dust extraction adapter



RED

RT-SS 120 L

Scroll Saw




ON/OFF switch

Stroke rate electronic

ON/OFF switch for LED-light

Flexible LED-Light for exactly illuminate of the work-piece



Laser for precise and straight cuts

Vacuum extractor unit adapter



ON/OFF switch for laser



Integrated saw dust blower facility

Saw table made of massive cast steel



Integrated tool compartment for saw blades



Saw table swivelling 2 x 45°



As special accessory available:
Spare saw blades (Set 5 pcs)

Art.No.:
45.062.00

Logistic Information

Technical Data

| | |
|---------------|--------------------|
| Type: | RT-SS 120 L |
| Art.-No.: | 43.090.31 |
| Ident-No.: | 01017 |
| Bar code: | 4006825 540048 |
| Packaging: | 670 x 280 x 420 mm |
| Sales unit: | 1 pc |
| 20'': | 320 pcs |
| 40'': | 680 pcs |
| 40'' HC: | -- pcs |
| Net weight: | 16.2 kg |
| Gross weight: | 18.3 kg |

| | |
|------------------------|-------------------------------|
| ■ Mains: | 230 V ~ 50 Hz |
| ■ Power: | 120 W S2 5 min |
| ■ No load speed: | 400 – 1,500 min ⁻¹ |
| ■ Stroke height: | 15 mm |
| ■ Saw blade length: | 127 mm |
| ■ Cutting height max.: | 50 mm / 90°; 20 mm / 45° |
| ■ Throat depth: | 405 mm |
| ■ Table size: | 420 x 270 mm |
| ■ Table swivelling: | 0° to 45° (right and left) |
| ■ Foot print: | 470 x 190 mm |

