



Einhell

CLASSIC

Impact Wrench (Pneumatic)

TC-PW 610 Compact

Item No.: 4138965

Ident No.: 21011

Bar Code: 4006825660630

The Einhell pneumatic impact wrench TC-PW 610 Compact is also suitable for demanding tasks with a maximum torque of 610 Nm. Thanks to its compact design, low weight and non-slip, rubberised handle, the impact wrench is comfortable to use, even during lengthy work. One-handed operation is possible thanks to the ergonomic left/right switch (one-stage/three-stage). The impact wrench has a 1/2" square drive. It delivers the best performance from an inner tube diameter of 9 mm. The delivery includes 3 sockets with plastic sleeve (17/19/21 mm), 1 oil bottle, 1 plug nipple and 10 m thread sealing tape in the transport and storage case.

Features & Benefits

- Powerful impact wrench with a max. torque of 610 Nm
- Thanks to its high performance, it is also suitable for demanding tasks
- The impact wrench has a 1/2" square drive
- Compact design for working in hard-to-reach areas
- Pleasant, long-lasting work possible thanks to low product weight
- One-hand operation thanks to ergonomic left/right switching
- Non-slip rubberised handle allows safe working
- Equipped with anti-clockwise (one-stage) and clockwise rotation (three-stage)
- Best performance from a hose inner diameter of 9 mm
- With 3 sockets with plastic sleeve in sizes 17/19/21 mm
- Incl. 1 oil bottle, 1 plug nipple and 10 m thread sealing tape
- Comes in a practical transport and storage case



Technical Data

- Max. torque (step 1) 120 Nm
- Max. torque (step 2) 230 Nm
- Max. torque (step 3) 610 Nm
- Operating pressure max. 8 bar
- No-load speed 9000 min⁻¹
- Air consumption 142 L/min
- Square drive 0.5 Inch

Logistic Data

- Product weight 1.14 kg
- Gross weight single packaging 2.55 kg
- Dimensions single packaging 280 x 230 x 74 mm
- Pieces per export carton 4 Pieces
- Gross weight export carton 10.3 kg
- Dimensions export carton 455 x 300 x 185 mm
- Container quantity (20"/40"/40"HC) 4400 | 9100 | 10280



AIR VOLUME HIGH

