

Powerful and robust dirt water pump to empty garden ponds, flooded basements and construction sites. It takes foreign particles up to $\varnothing 30$ mm in size. The pump is equipped with a float switch for automatic ON/OFF – operation for a varying water level. The housing is made of an impact resistant plastic.

Features

- Handle (1)
- Universal connection for 25 mm (1") and 32 mm (1 ¼") male thread hose connection as well as approx. 33.3 mm (G1) male thread (2)
- 90 ° angel bracket with approx. 47.8 mm (G1 ½) AG x approx. 47.8 mm (G1 ½) male thread (3)
- Float switch (4)

Technical Data

- Mains: 230 V ~ 50 Hz
- Power: 350 W
- Delivery quantity max.: 7,000 l/h
- Delivery height max.: 5 m
- Immersions depth max.: 5 m
- Water temperature max.: 35°C
- Connection hose: approx. 47.8 mm (G1 ½) female thread
- Foreign particle size up to: $\varnothing 30$ mm
- Mains cable: 10 m
- ON function: approx. 50 cm
- OFF function: approx. 5 cm
- Exhaust height: approx. 40 mm
- Product weight: 4.2 kg

Logistic Data

- Net weight: 4.3 kg
- Gross weight: 4.7 kg
- Packing dimensions: 220 x 160 x 340 mm
- Bar code: 4006825 596229
- Sales Unit: 4 pcs

